




# GANCI di SICUREZZA GIREVOLI, ad OCCHIO e per FONDERIA

Accessori per imbrache GRADO 80


www.incofil.com



## GANCIO DI SICUREZZA GIREVOLE

Codice	catena		misure							peso	W.L.L.
	Ø mm	Inch	R mm	A	B	O	D	G	H	Kg	Kg
IRG 06	6	1/4	150	28	23	33	11	15	20	0,6	1120
IRG 08	7-8	9/32-5/16	185	34	27	37	13	19	24	1,1	2000
IRG 10	10	3/8	217	45	35	42	16	23	30	2,0	3150
IRG 13	13	1/2	271	54	43	48	21	27	40	4,0	5300
IRG 16	16	5/8	334	62	58	62	22	37	49	6,8	8000


W.L.L.: carico max di utilizzo



## GANCIO DI SICUREZZA AD OCCHIO

Codice	catena		misure							peso	W.L.L.
	Ø mm	Inch	A mm	D	G	H	O	R	T	Kg	Kg
IRO 06	6	1/4	28	11	16	21	21	109	35	0,510	1120
IRO 08	7-8	9/32-5/16	34	12	20	26	25	135	43	0,936	2000
IRO 10	10	3/8	45	16	25	30	33	168	56	1,626	3150
IRO 13	13	1/2	51	20	35	40	40	205	69	3,250	5300
IRO 16	16	5/8	60	27	36	50	50	251	80	6,050	8000

W.L.L.: carico max di utilizzo



## GANCIO PER FONDERIA

Codice	catena		misure						peso	W.L.L.
	Ø mm	Inch	A mm	D	G	H	O	R	Kg	Kg
IY 08	7-8	9/32-5/16	64	13,5	25	29	18	131	0,92	2000
IY 10	10	3/8	76	14	23	30	32	150	1,77	3150
IY 13	13	1/2	89	19	38	40	27	191	2,82	5300
IY 16	16	5/8	102	24	45	48	47	205	5,03	8000

W.L.L.: carico max di utilizzo